



# MPQ4214

## 40V, USB Type-C PD

### Synchronous Buck-Boost Controller with I<sup>2</sup>C

### AEC-Q100 Qualification in Progress

**PRELIMINARY SPECIFICATIONS SUBJECT TO CHANGE**

## DESCRIPTION

The MPQ4214 is a full-feature, buck-boost controller to support USB PD3.0 power solutions for automotive USB power designs. The MPQ4214 is a synchronous, four-switch, buck-boost controller capable of regulating different output voltages with a wide input voltage range and high efficiency. The MPQ4214 provides an I<sup>2</sup>C interface, which supports V<sub>OUT</sub> voltage programmability, V<sub>OUT</sub> slew-rate control and constant output current limit programmability, making the MPQ4214 suitable for USB power delivery (PD) design in USB Type-C power supplies.

The MPQ4214 uses valley-current control in buck mode and peak-current control in boost mode, providing fast load transient response and smooth buck-boost mode transient. The MPQ4214 provides forced continuous conduction mode (FCCM) and programmable average current limit, which supports flexible designs for different applications.

The MPQ4214 also features hiccup over-current protection (OCP), hiccup over-voltage protection (OVP), programmable soft start, and programmable under-voltage lockout (UVLO).

The MPQ4214 is available in a QFN-27 (5mmx5mm) package.

## FEATURES

- 6V to 40V Startup Input Voltage Range
- 4V to 40V Operation Input Voltage Range
- Flexible I<sup>2</sup>C Interface Control for:
  - 3V to 20V Output with 10mV Steps
  - Selectable V<sub>OUT</sub> Slew Rate
  - Programmable Constant Current Limit
- <50mA Steps Current Limit Adjusting through IPWM Pin
- Frequency Dithering Function for EMI Optimization
- Integrated V<sub>OUT</sub> Discharge Function
- Selectable 200kHz, 300kHz, 400kHz, and 600kHz Switching Frequency
- Fixed Frequency over Full Load Range with FCCM Mode
- OCP, SCP, and OVP
- Interrupt Indicator for OCP, OVP and OTP
- Available in a QFN-27(5mmx5mm) Package
- AEC-Q100 Qualification in Progress

## APPLICATIONS

- USB Power Delivery
- Industrial PC Power Supplies
- Automotive Start-Stop Systems
- Super-Capacitor Charging

All MPS parts are lead-free, halogen-free, and adhere to the RoHS directive. For MPS green status, please visit the MPS website under Quality Assurance. "MPS" and "The Future of Analog IC Technology" are registered trademarks of Monolithic Power Systems, Inc.

## TYPICAL APPLICATION

